



Special application for BCM pumps

Example of Inverter system, Timer and servo ventilation



Example of portable self-powered acoustic warning device with external optional management



Example of actuator (sprinkler) controlled by Inverter digital



Example of pedal control (start and stop)



CARATTERISTICHE TECNICHE:

- Typically adaptable and installable on any type of BCM pump with AISI stainless steel trolley (mod.30-40-50-60-70-80-100 also with variator).
- Simplicity in the use and management of the intended function
- Manuals and guidance on the use of the device and its functions
- Visual diagnostics of the operation and status of the pump.
- Manual pump start function
- Protection in case of lack of input phase
- Possibility of connection on EXT connector to various configurable options.
- Power supplies available: three-phase 380 Vac, single-phase 220Vac, +24 Vac, +15 Vac
- INOX for pump without reset
- Powers available up to 15 kW with direct start
- Higher powers with the use of inverters
- Dimension of the electrical panel depending on the functions

Accessories, spare parts, maintenance and dedicated technical assistance

Company site



Where to access



B.C.M. Macchine Enologiche

Via Veneto 10 Zona Artigianale Saonara (PD)

Tel +39 049-640372 Fax +39 049-5018355

Marketing & Service:

info@bcmenologia.com

www.bcmenologia.com